

# Cordless Brushless Impact Driver PJID143

# MAX<sup>®</sup>

## Smallest and Most Powerful in its class!!

### Sleeve Protector (PAT.P)

Prevents damages to work piece surface.



Smooth variable speed control trigger

Built-in LED light



### Consistent high speed performance

- Regular impact driver slows down as the battery charge gets lower.
- MAX-PJID143 maintains same speed even when the charge becomes lower due to the voltage control feature.



Only 29mm

Only 135mm

Durable DC Brushless motor


Reverse switch

Comfortable rubber grip

30-Minute rapid charge battery



Belt hook



### TOOL SPECIFICATIONS

| PRODUCT NO.           | PJID143  | PJID143 W/O BC                             |
|-----------------------|--|--|
| DIMENSIONS            | 236(H)×82(W)×135(L)mm 9-1/4"×3-1/4"×5-1/4"   | 236(H)×82(W)×135(L)mm 9-1/4"×3-1/4"×5-1/4" |
| WEIGHT                | 1.45kg (3.2lbs) (Battery included)   | 1.45kg (3.2lbs) (Battery included)         |
| MOTOR                 | Brushless DC Motor   |  |
| NO-LOAD SPEED         | 0~2,600 min <sup>-1</sup>  |  |
| IMPACT RATE           | 0~2,500 min <sup>-1</sup>  |  |
| RATED VOLTAGE/BATTERY | 14.4V, Li-ion Battery pack JPL914  |  |
| BATTERY CHARGER       | JC928(CE)  |  |
| NOISE                 | The typical A-weighted noise level determined according to EN60745-2-2:<br>●Sound pressure level(L <sub>PA</sub> ): 88dB(A) ●Sound power level(L <sub>WA</sub> ): 99dB(A) ●Uncertainty(K): 3dB(A)  |  |
| VIBRATION             | The vibration total value (tri-axial vector sum) determined according to EN60745-2-2:<br>●Work mode: Impact tightening of fasteners of the maximum capacity of the tool.<br>●Vibration emission value(a <sub>h</sub> ): 9.6m/s <sup>2</sup> ●Uncertainty(K): 1.5m/s <sup>2</sup> |  |

### STANDARD EQUIPMENT

- Battery pack JPL914 (1pc.)
- AC Battery charger JC928(CE)
- Plastic carry case
- Belt hook



Comes with plastic carry case

| BATTERY | Battery pack JPL914          | BATTERY CHARGER | JC928(CE)   |
|---------|------------------------------|-----------------|---|
| WEIGHT  | 0.5 kg (1.1 lbs)             | WEIGHT          | 1.6kg (3.5 lbs)   |
| TYPE    | Lithium ion battery          | INPUT           | AC100-240V 50/60Hz 1.62-0.68A   |
| VOLTAGE | DC14.4V(3.6V×4cells)(3.0 Ah) | RECHARGE TIME   | Quick charging-Approx. 30 minutes(90% of capacity)<br>Full charging-Approx. 45 minutes at 25 C (100% of capacity) |



The specifications and design of the products in this catalog will be subject to change without advance notice due to our continuous efforts to improve the quality of our products.

### MAX CO.,LTD.

6-6 NIHONBASHI HAKOZAKI-CHO, CHUO-KU, TOKYO, JAPAN  
PHONE: 81-3-3669-8131 FAX: 81-3-3669-7104  
Web: <http://www.max-ltd.co.jp/int/>

Distributor: