# **Cordless Rotary Hammer**



# **FEATURES**

# Best-in-class cordless rotary hammer in drilling speed.

Thanks to Sensor-less Brushless Motor installed, PJR265 provides you with the fastest speed in its class.

# More powerful impact with 25.2V battery using unique mechanism v.s. conventional 36V-battery models.

New "Impact Generating Mechanism" desi faster drilling speed than any other 36V battery-powered model.

igned by N	AX provides more	powerful impact and
Impact energy comparison		(Unit:Jules)
PJR265	Brand A (28.8V)	Brand B (36.0V)
3.4J	2.4J	3.0J

**Chuck for SDS** 

**Plus Bit** 





RP

110

100

90

80 70

60

50

ollino

# More holes per charge.

movement under friction

PJR265

Energy saving Brushless Motor equals job productivity with light-weight 25.2V Lithium-ion battery.

#### Stable and consistent performance. Δ

100%

► 76.4%

Regular rotary Drilling

sistently provides the RPM at 100% performance



Concrete hardness : 350kgf/cm<sup>2</sup>

**Safety Clutch** 

PJR265 consistently provides the RPM at 100% performance ratio with our inverter control regardless of the material hardness.

## **Drilling Mode Lever**

- Rotation / Rotation Drilling 2 modes
- Push button prevent from false operation

#### •Forward/ **Reverse switch**

#### **Comfotable rubber** grip

Easy to grip and tireless

### Variable speed trigger switch



LED light ······

#### Normal / Low impact ····· drilling mode selectable

#### LED mode status monitor

Green: Low impact mode Light off: Normal impact mode Red: Stand by mode (Protect moter from buming) Blinking green: Maintenance mode (Time for maintenance)

#### Lithium-ion rechargeable battery 25.2V 3.0Ah



# **TOOL SPECIFICATIONS**

Product name	PJR265(CE) Cordless Rotary Hammer	
Bit type	SDS PLUS	
Voltage/Battery	Lithium-ion rechargeable battery 25.2V 3.0Ah	
RPM	0~560RPM (Low mode) 0~920RPM (Normal mode)	
Impact rate	0~2,860BPM (Low impact mode) 0~4,700BPM (Normal impact mode)	
Maximum Drilling Diameter	Concrete: Ø26mm Steel: Ø13mm Wood: Ø30mm	
Motor	Brushless DC motor	
Size	L 332mm × H 210mm × W 82mm (Inc. Battery pack)	
Weight	3.7kg (Inc. Battery pack)	
Accessories	Battery pack (JP-L925) 2-pcs Battery charger (JC-928) Side handle · Depth Gauge Instruction manual - Carrying case	

The specifications and design of the products in this catalog will be subject to change without advance notice due to our continuous efforts to improve the quality of our products.



6-6 NIHONBASHI HAKOZAKI-CHO,CHUO-KU,TOKYO,JAPAN PHONE: 81-3-3669-8131 FAX: 81-3-3669-7104 Web:http://www.max-ltd.co.jp/int/

Distributor: